

REPLACEMENT PARAGRAPHS IN SPECIFICATION

Turning now to the drawings and more particularly to figure 1 we have a perspective view of a bicycle trailer 20 hitched to a bicycle frame 22. The bicycle trailer 20 comprises: a trailer frame 24 having two rectangular members 26, each rectangular member 26 having opposite end portions which are centrally and pivotally attached 29 to the opposite end portions of the other rectangular member 26; and each rectangular member 26 having a lower side portion extending generally horizontally along one lower side portion of the trailer 20 and an upper side portion extending generally horizontally along an upper side portion of the trailer 20. Upright releasable spacing limitation maintenance means, which most preferably comprises a at least one strap 28 which extends between the two rectangular members 26 to restrain the frame 24 from laterally compressing and heightening. The limitation means is releasable so that the trailer 20 can be laterally collapsed merely by releasing the strap 28. A tongue member 30 has a rear end portion attached to a front end portion of the trailer frame 24; a central portion extending forwardly, and a front portion. A releasable hitch 32 has a bicycle frame mounted portion 34 which is carried by the bicycle frame 22, and a releasable portion 36 which is attached to the front portion of the tongue member 30. A trailer bottom portion 40 extends between the lower side portions of the rectangular frame members 26. Two wheels are each rotatably mounted to opposite central portion of the lower side portion of the trailer frame 26.